

## shower valves - CoolFlo Safe Touch Thermostatic Bar Shower

**gives total control**



### Introduction

The CoolFlo Safetouch Thermostatic Bar Shower, featuring Inta's proven Anti Scald technology and a cool touch body which maintains a safe surface temperature of the shower valve. Combined with the contemporary shower kit with a multi-function shower head the CoolFlo shower will bring style and safety to any bathroom

- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of  $\pm 2^{\circ}\text{C}$
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.2 to 5 bar

### Product Range

Description	Code	List Price (exc VAT)
CoolFlo safe touch thermostatic bar shower with flexible slide rail kit	ST20017CP	£133.13
CoolFlo safe touch thermostatic bar shower	ST20015CP	£75.82
Flexible slide rail kit	31770CP	£71.52

CoolFlo safe touch thermostatic bar shower with flexible slide rail kit  
ST20017CP



## shower valves - CoolFlo Safe Touch Thermostatic Bar Shower

### Features

#### Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	G 3/4" F BSP (valve body)
Outlet Connections	G 1/2" BSP
Min Temperature differential to achieve hot or cold failsafe	15°C

System Installation: Unvented, Pressurised, Gravity and Combination Boilers

